



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

Bottom Mount Reach-In Refrigerators

Standard Features

- Bottom mount compressor units with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Electronic Temperature Controller
- Maintains temperatures between 33°F to 40°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three(3) pre-installed shelves per section
- Down duct refrigeration to ensure even distribution of air

Optional Accessories

- Extra shelves – includes 4 shelf clips per shelf
MBF8505GR shelf part #: W0402393
MBF8507GR shelf part #: W0402387
MBF8508GR shelf part #: W0402387 left/right shelf,
part #: W0402388 middle shelf

For the best results of food preservation we recommend setting your refrigerator between 33°F to 38 °F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

MODELS:

MBF8505GR / MBF8506GR / MBF8507GR / MBF8508GR



MBF8505GR



MBF8506GR



MBF8507GR



MBF8508GR



2 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY



MBF8505GR/MBF8505GRL
MBF8507GR/MBF8508GR

REV. 10/23



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com



California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

SPECIFICATIONS



| Models | Door | Capacity (Cu.Ft.) | Shelves | Casters (inch) | Rated Current (A) | Voltage (V/Hz/Ph) | HP | Refrigerant | Exterior Dimensions (inch) | Net Weight (lbs) | Gross Weight (lbs) |
|-----------|------|-------------------|---------|----------------|-------------------|-------------------|-----|-------------|--|------------------|--------------------|
| MBF8505GR | 1 | 19.1 | 3 | 4 | 2.1 | 115/60/1 | 1/7 | R290 | 27×31 ^{7/10} ×83 ^{1/10} | 249 | 282 |
| MBF8506GR | 2 | 28.5 | 6 | 4 | 3.2 | 115/60/1 | 1/5 | R290 | 39 ^{1/2} ×31 ^{7/10} ×83 ^{1/10} | 317 | 365 |
| MBF8507GR | 2 | 43.8 | 6 | 4 | 3.2 | 115/60/1 | 1/5 | R290 | 54 ^{2/5} ×31 ^{7/10} ×83 ^{1/10} | 397 | 452 |
| MBF8508GR | 3 | 68 | 9 | 4 | 4.2 | 115/60/1 | 1/4 | R290 | 81 ^{9/10} ×31 ^{7/10} ×83 ^{1/10} | 538 | 615 |

PLAN VIEW



MBF8505GR






MBF8506GR



MBF8507GR



MBF8508GR



*Interior Dimensions

SELF-CLOSING
AND STAY OPEN
DOOR FEATURE

Casters

Epoxy shelves


Door lock

Down duct

Temperature control



NEMA 5-15P



NEMA
15A/125V